




I-line Clamps

Heavy Duty I-Line Clamps - 13ILH




Tube O.D.	Dimension A	Service Pressure Rating at 70°F *	Service Pressure Rating at 250°F *	Part Number
1"- 1½"	2.122	700 PSI	250 PSI	13ILH100-150
2"	2.654	450 PSI	250 PSI	13ILH200
2½"	3.185	450 PSI	200 PSI	13ILH250
3"	3.717	350 PSI	150 PSI	13ILH300
4"	4.820	200 PSI	125 PSI	13ILH400
6"	7.689	150 PSI	100 PSI	13ILH600
8"	9.689	125 PSI	75 PSI	13ILH800

* Wing nuts tightened to 25 inch lbs of torque

G


Bolted I-Line Clamps - 13ILB



Single bolt design

Tube O.D.	Dimension A	Service Pressure Rating at 70°F *	Service Pressure Rating at 250°F *	Part Number
1"- 1½"	2.122	1220 PSI	1100 PSI	13ILB100-150
2"	2.654	900 PSI	830 PSI	13ILB200
2½"	3.185	720 PSI	660 PSI	13ILB250
3"	3.717	600 PSI	550 PSI	13ILB300
4"	4.820	570 PSI	525 PSI	13ILB400

* The nuts must be tightened to 20 ft.lbs.



Two bolt design

Tube O.D.	Dimension A	Service Pressure Rating at 70°F *	Service Pressure Rating at 250°F *	Part Number
6"	7.689	300 PSI	200 PSI	13ILB600
8"	9.689	250 PSI	150 PSI	13ILB800

* The nuts must be tightened to 20 ft.lbs.